

KBTI9L4VN

Product family	Hood
Hood Type	Decorative island hood
Design	T flat
Extraction	Extraction
Electronic control	Yes
Material	Stainless Steel + Glass
Type of steel	Brushed
EAN code	8017709305741
Hood width	90 cm
Aesthetic	Universale
Colour	Stainless steel
Finishing	Satin
Logo	Silk screen



Controls



Control setting	Touch control	Led color	White
-----------------	---------------	-----------	-------

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	
Auto-vent 2.0	

Technical Features



No. of lights	2	No. of filters	3
Light type	LED	Anti-grease filters	Aluminium
Light Power	7.3 W	Filter replacement indicator	Yes
Dimmer mode	Yes	Vent outlet	150 mm
Light color temperature range	3000 - 5700 K	Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	820 m³/h	Minimum distance from ELECTRIC hob	650 mm
Motor power	275 W	Non return valve	Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	280	48
Speed 2	415	59
Speed 3	626	69
Intensive speed	778	74

Accessories included

Tube reduction Yes

Performance / Energy Label



Annual Efficiency Consumption (AEChood) 49 kWh/a

Energy efficiency class (EEC) A

Fluid Dynamic Efficiency (FDE) 35.4

Fluid Dynamic Efficiency class (FDEC) A

Lighting Efficiency (LE) 23.5 lux/W

Lighting Efficiency Class (LEC) B

Grease Filtering Efficiency (GFE) 77.4 %

Grease Filtering Efficiency Class (GFEC) C

Air flow at minumum speed (Qmin) 280 m³/h

Air flow at maximum speed (Qmax) 626 m³/h

Air flow at boost speed (Qboost) 778 m³/h

Airbourne acoustical A- weighted sound Power Emission at minimum speed (SPEmin) 47 dBA

Airborne acoustical A- weighted sound Power Emission at maximum speed (SPEmax) 69 dBA

Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost) 73 dBA

Energy Efficiency Index 46.4

Measured air flow rate at best efficiency point (Qbep) 397 m³/h

Measured air pressure at best efficiency point (Pbep) 474 Pa

Measured electric power input at best efficiency point (Wbep) 175 W

Nominal Power consumption of the light system (WL) 15 W

Average illumination of the light on the cooking surface (Emiddle) 348 lux

Sound power level at highest setting (Lwa) 69 dBA


Electrical Connection

Voltage 220-240 V
Frequency (Hz) 50-60 Hz

Power supply cable length 1500 mm

Plug

Not present




Compatible Accessories




KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



KITFCKBT

1 pc of charcoal filter for the hood models KBT* / KBCT*



KITFCKBTR

1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

Symbols glossary

	24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.		Energy efficiency class A
	Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.		Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.
	Warning light(s): to advise when filters need changing.		Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.
	Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button.		Intensive/turbo setting: when extra fast extraction is required.
	Connection between hob and hood		Dimmering Lights
	Tunable white from warm to cold.		