

# KD90HNE

|                   |                      |
|-------------------|----------------------|
| Product family    | Hood                 |
| Hood Type         | Decorative wall hood |
| Design            | Chimney              |
| Extraction        | Extraction           |
| Material          | Painted material     |
| Type of steel     | Brushed              |
| EAN code          | 8017709243609        |
| Hood width        | 90 cm                |
| Aesthetic         | Classica             |
| Colour            | Black                |
| Finishing         | Glossy               |
| Serigraphy colour | Black                |
| Logo              | Applied              |



## Controls

|                 |               |                 |              |
|-----------------|---------------|-----------------|--------------|
| Control setting | Control knobs | Control knobs   | Classic      |
| No. of controls | 2             | Controls colour | Steel effect |

## Program / Functions

|                 |                                                                                     |
|-----------------|-------------------------------------------------------------------------------------|
| No. of speeds   | 3                                                                                   |
| Intensive speed |  |

## Technical Features

|                                                                                    |                                                                                     |                                    |                 |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------|-----------------|
|  |  |                                    |                 |
| No. of lights                                                                      | 2                                                                                   | No. of filters                     | 3               |
| Light type                                                                         | LED                                                                                 | Anti-grease filters                | Stainless steel |
| Light Power                                                                        | 1 W                                                                                 | Vent outlet                        | 150 mm          |
| Light color temperature scale (K)                                                  | 4000 K                                                                              | Minimum distance from GAS hob      | 750 mm          |
| Free outlet maximum capacity                                                       | 815 m³/h                                                                            | Minimum distance from ELECTRIC hob | 650 mm          |
| Motor power                                                                        | 275 W                                                                               | Non return valve                   | Yes             |

|         | Extraction rate IEC 61591 [m³/h] | Noise level IEC 60704-2-13 [dBA] |
|---------|----------------------------------|----------------------------------|
| Speed 1 | 288                              | 48                               |
| Speed 2 | 421                              | 63                               |

|                 |     |    |
|-----------------|-----|----|
| Speed 3         | 630 | 67 |
| Intensive speed | 781 | 72 |

## Performance / Energy Label



|                                          |            |                                                                                |          |
|------------------------------------------|------------|--------------------------------------------------------------------------------|----------|
| Annual Efficiency Consumption (AEChood)  | 40 kWh/a   | Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) | 48 dBA   |
| Energy efficiency class (EEC)            | A+         | Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)  | 67 dBA   |
| Fluid Dynamic Efficiency (FDE)           | 36.2       | Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) | 72 dBA   |
| Fluid Dynamic Efficiency class (FDEC)    | A          | Time increase factor (F)                                                       | 1.00     |
| Lighting Efficiency (LE)                 | 78.2 lux/W | Measured air flow rate at best efficiency point (Qbep)                         | 413 m³/h |
| Lighting Efficiency Class (LEC)          | A          | Measured air pressure at best efficiency point (Pbep)                          | 476 Pa   |
| Grease Filtering Efficiency (GFE)        | 78.5 %     | Measured electric power input at best efficiency point (Wbep)                  | 151 W    |
| Grease Filtering Efficiency Class (GFEC) | C          | Nominal Power consumption of the light system (WL)                             | 2 W      |
| Air flow at minumum speed (Qmin)         | 288 m³/h   | Average illumination of the light on the cooking surface (Emiddle)             | 172 lux  |
| Air flow at maximum speed (Qmax)         | 630 m³/h   | Sound power level at highest setting (Lwa)                                     | 67 dBA   |
| Air flow at boost speed (Qboost)         | 781 m³/h   |                                                                                |          |


## Electrical Connection

|                              |           |                           |             |
|------------------------------|-----------|---------------------------|-------------|
| Electrical connection rating | 277 W     | Power supply cable length | 1000 mm     |
| Voltage                      | 220-240 V | Plug                      | Not present |
| Frequency (Hz)               | 50-60 Hz  |                           |             |

## Also available

|                               |                             |                   |                   |
|-------------------------------|-----------------------------|-------------------|-------------------|
| Alternative colours available | Stainless steel, Anthracite | Available colours | KD90HXE - KD90HAE |
|-------------------------------|-----------------------------|-------------------|-------------------|

## Optional accessories



---

## Compatible Accessories

---



### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary

---



A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.