

KI120XE

Product family	Hood
Hood Type	Decorative island hood
Design	T flat
Extraction	Extraction
Electronic control	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709204051
Hood width	120 cm
Aesthetic	Universale
Colour	Stainless steel
Finishing	Satin
Logo	Embossed



Controls

Control setting	Electronic buttons	Led color	White
-----------------	--------------------	-----------	-------

Program / Functions

No. of speeds	3
Intensive speed	
Time-setting options	

Technical Features

				
No. of lights	4	Anti-grease filters	Aluminium	
Light type	LED	Filter replacement indicator	Yes	
Light Power	1 W	Vent outlet	150 mm	
Light color temperature scale (K)	4000 K	Minimum distance from GAS hob	750 mm	
Free outlet maximum capacity	820 m³/h	Minimum distance from ELECTRIC hob	650 mm	
Motor power	275 W	Non return valve	Yes	
No. of filters	4			

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	316	48

Speed 2	385	59
Speed 3	529	62
Intensive speed	783	70

Accessories included

Tube reduction Yes

Performance / Energy Label




Annual Efficiency Consumption (AEChood) 64 kWh/a
Energy efficiency class (EEC) B
Fluid Dynamic Efficiency (FDE) 28.7
Fluid Dynamic Efficiency class (FDEC) A
Lighting Efficiency (LE) 70.9 lux/W
Lighting Efficiency Class (LEC) A
Grease Filtering Efficiency (GFE) 79.8 %
Grease Filtering Efficiency Class (GFEC) C
Air flow at minumum speed (Qmin) 316 m³/h
Air flow at maximum speed (Qmax) 529 m³/h
Air flow at boost speed (Qboost) 783 m³/h

Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin) 48 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 62 dBA
Airbourne acouistical A-weighted sound power emission at boost speed (SPEboost) 70 dBA
Time increase factor (F) 1.00
Energy Efficiency Index 58.7
Measured air flow rate at best efficiency point (Qbep) 394 m³/h
Measured air pressure at best efficiency point (Pbep) 449 Pa
Measured electric power input at best efficiency point (Wbep) 171 W
Nominal Power consumption of the light system (WL) 4 W
Average illumination of the light on the cooking surface (Emiddle) 312 lux
Sound power level at highest setting (Lwa) 62 dBA

Electrical Connection

Electrical connection rating	279 W	Power supply cable length	1500 mm
Voltage	220-240 V	Plug	Not present
Frequency (Hz)	50-60 Hz		



Compatible Accessories



FLT6

Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Warning light(s): to advise when filters need changing.



Intensive/turbo setting: when extra fast extraction is required.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.

