

# KSED95XE

|                |                      |
|----------------|----------------------|
| Product family | Hood                 |
| Hood Type      | Decorative wall hood |
| Design         | Chimney              |
| Extraction     | Extraction           |
| Material       | Stainless steel      |
| Type of steel  | Brushed              |
| EAN code       | 8017709206109        |
| Hood width     | 90 cm                |
| Aesthetic      | Universale           |
| Colour         | Stainless steel      |
| Finishing      | Satin                |
| Logo           | Embossed             |



## Controls

|                 |        |
|-----------------|--------|
| Control setting | Slider |
|-----------------|--------|

## Program / Functions

|               |   |
|---------------|---|
| No. of speeds | 3 |
|---------------|---|

## Technical Features

|                                                                                    |                                                                                     |                                    |           |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------|-----------|
|  |  |                                    |           |
| No. of lights                                                                      | 2                                                                                   | No. of filters                     | 3         |
| Light type                                                                         | LED                                                                                 | Anti-grease filters                | Aluminium |
| Light Power                                                                        | 1 W                                                                                 | Vent outlet                        | 150 mm    |
| Light color temperature scale (K)                                                  | 4000 K                                                                              | Minimum distance from GAS hob      | 750 mm    |
| Free outlet maximum capacity                                                       | 595 m³/h                                                                            | Minimum distance from ELECTRIC hob | 650 mm    |
| Motor power                                                                        | 200 W                                                                               | Non return valve                   | Yes       |

|         | Extraction rate IEC 61591 [m³/h] | Noise level IEC 60704-2-13 [dBA] |
|---------|----------------------------------|----------------------------------|
| Speed 1 | 328                              | 50                               |
| Speed 2 | 420                              | 57                               |

|            |     |    |
|------------|-----|----|
| Speed<br>3 | 588 | 65 |
|------------|-----|----|

## Performance / Energy Label




|                                          |            |                                                                                |          |
|------------------------------------------|------------|--------------------------------------------------------------------------------|----------|
| Annual Efficiency Consumption (AEChood)  | 54 kWh/a   | Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) | 50 dBA   |
| Energy efficiency class (EEC)            | B          | Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)  | 65 dBA   |
| Fluid Dynamic Efficiency (FDE)           | 25.3       | Time increase factor (F)                                                       | 1.1      |
| Fluid Dynamic Efficiency class (FDEC)    | B          | Energy Efficiency Index                                                        | 61.2     |
| Lighting Efficiency (LE)                 | 74.3 lux/W | Measured air flow rate at best efficiency point (Qbep)                         | 318 m³/h |
| Lighting Efficiency Class (LEC)          | A          | Measured air pressure at best efficiency point (Pbep)                          | 375 Pa   |
| Grease Filtering Efficiency (GFE)        | 70.8 %     | Measured electric power input at best efficiency point (Wbep)                  | 131 W    |
| Grease Filtering Efficiency Class (GFEC) | D          | Nominal Power consumption of the light system (WL)                             | 2 W      |
| Air flow at minumum speed (Qmin)         | 328 m³/h   | Average illumination of the light on the cooking surface (Emiddle)             | 164 lux  |
| Air flow at maximum speed (Qmax)         | 588 m³/h   | Sound power level at highest setting (Lwa)                                     | 65 dBA   |

## Electrical Connection

|                              |           |                           |             |
|------------------------------|-----------|---------------------------|-------------|
| Electrical connection rating | 202 W     | Power supply cable length | 1000 mm     |
| Voltage                      | 220-240 V | Plug                      | Not present |
| Frequency (Hz)               | 50-60 Hz  |                           |             |

## Also available

|                               |                                    |                   |                                             |
|-------------------------------|------------------------------------|-------------------|---------------------------------------------|
| Alternative colours available | Black, Anthracite, Cream, Red Wine | Available colours | KSED95NEE - KSED95AE - KSED95PE - KSED95RWE |
|-------------------------------|------------------------------------|-------------------|---------------------------------------------|



---

## Compatible Accessories

---



### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary

---



**Filters:** Model has filters to help remove grease from the steam emanating from the pans during cooking.



**Lights:** All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.

