

LLR862-2

Sink material	Stainless steel
Type	Welded sink
No. of bowls	2
EAN code	8017709282424



Aesthetics

	Aesthetic	Universale	Building in type	Ultra-low profile
	Colour	Stainless steel	Logo	Embossed
	Finishing	Brushed	Tap hole / precut tap hole	2 Tapholes
	Series	Alba		

	Bowl type RH	Bowl thickness (mm)	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner right bowl (mm)	Overflow	Strainer position	Strainer dimension
RH Bowl	Traditional	0.7	340 x 400 x 210	210	80	Yes, traditional	Wall position	3.5"
LH Bowl	Traditional	0.7	340 x 400 x 210	210	80		Wall position	3.5"

Technical Features


	Frame thickness	0.7 mm	Tap hole	2
	Frame depth (mm)	15	Tap hole diameter	35 mm
	Dimensions of the product (mm)	225x860x500 mm	Popup command	Yes, double
	Cutout dimension topmount (mm)	840 x 480 mm	Dividing wall width	40 mm
	Undermount cutout radius	10 mm	Gasket type	Sealing paste
			No. of clips	8
			Type of clips	Standard

Height from kitchen top 6 mm
Base unit size 90 cm

Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips, Gasket, Automatic pop - up with round rotary control



Compatible Accessories



3713

Siphon double bowls sinks (dishwasher connection included)



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



DB34

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



STABMIX

Tap stabiliser



CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

Symbols glossary



Cupboard width required for sink installation.



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Ultra-low profile: Installation of product with flat edge - height of 1 mm.